



Trassig Corp.  
www.trassig.com  
info@trassig.com  
203-659-0456  
65 Redding Rd. #874  
Georgetown CT 06829

## Deck Repair Kit Instructions

This product cures very quickly once the container seal is broken. Only open the container if you plan on using it immediately after (within a few minutes). The shelf life of the unopened container once shipped is approximately 12 months. If you are repairing any vertical surfaces, we recommend using our aliphatic binder as a primer. Once applied, the product will set within a couple hours. If you need any further help, call: 203-659-0456 or email [info@trassig.com](mailto:info@trassig.com).

### Coverage

A 32 oz can will cover roughly 8 sf depending on the thickness applied.

### Installation Steps (Watch the install video on [trassig.com](http://trassig.com))

1. Perform all your site prep, whether you are cleaning dust from the area, grinding the metal, cutting loose rubber pieces away or neutralizing rust. Make sure this is all done before you open the can. Peel away all the loose plastisol rubber from the deck first.
2. Choose a warm dry day for the repair. Minimum of 50 degrees temperature and no anticipated rain for the rest of the day.
3. If you are using our aliphatic primer for vertical surfaces, apply a thin layer of primer with a brush and let it set for about an hour before you apply the deck repair.
4. Use a putty knife to apply the deck repair material evenly on the surface. You can apply more than one coat as long as you let the last coat cure first.
5. The product normally cures in 3 hours or less in most conditions. If you are in colder, less humid climate, allow for double the drying time for the product to cure
6. You can sand or spray paint the new surface if you want to. (2X Rust-oleum works well)